

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

AMENDMENT TO THE CLAIMS

WHAT IS CLAIMED IS:

1. (Currently Amended) A continuous on-line carbon analyzer for water applications, the analyzer comprising:
 - a sample inlet to receive a continuous stream of sample specimen;
 - a gas inlet to receive a continuous stream of gas that is substantially free of carbon dioxide;
 - a sample stream flow controller including a metering pump coupled to the sample stream and adapted to control sample flow therethrough;
 - a gas flow controller coupled to the gas stream and adapted to control gas flow therethrough;
 - a combustion furnace coupled to the sample stream flow controller and the gas flow controller to receive continuous flow of sample stream and gas, the combustion furnace being maintained at a temperature in excess of approximately 680°C;
 - a chiller coupled to the combustion furnace to receive the oxidized material and condense water and particulate matter from the heated materials; and
 - a detector coupled to the chiller to receive a continuous flow of carbon dioxide and provide an output indicative of a relative amount of carbon dioxide flowing therethrough.
2. (Previously Amended) The analyzer of claim 1 and further comprising a catalyst disposed in the combustion furnace.
3. (Original) The analyzer of claim 2 wherein the catalyst is a platinum-based catalyst.
4. (Cancelled)

5. (Currently Amended) The analyzer of claim 14 wherein the metering pump provides a sample flow in the range of approximately 0.5 cc per minute to approximately 2.0 cc per minute.
6. (Original) The analyzer of claim 5 wherein the sample flow is approximately 0.5 cc per minute.
7. (Original) The analyzer of claim 1 wherein the chiller is a thermoelectric chiller.
8. (Original) The analyzer of claim 1 wherein the detector is a non-dispersive infrared detector.
9. (Original) The analyzer of claim 8 wherein the non-dispersive infrared detector provides an output corresponding to carbon dioxide quantity in the zero to 100 parts per million range.
10. (Original) The analyzer of claim 1 wherein the output is indicative of total carbon in the sample stream.
11. (Original) The analyzer of claim 1 wherein the output is indicative of the total organic carbon in the sample stream.
12. (Currently Amended) A method of continuously analyzing total carbon content in water, the method comprising:
 - continuously receiving a sample specimen and providing the sample specimen at a pre-selected flow rate;
 - receiving carbon dioxide-free gas at a pre-selected flow rate;

conveying the sample stream and gas through a
combustion furnace to oxidize the sample stream;
and
measuring a quantity of carbon dioxide generated by the
combustion furnace which quantity is indicative of
the total carbon of the water.

13. (Original) The method of claim 12 and further
comprising cooling the oxidized sample stream prior to the step
of measuring carbon dioxide quantity.

14. (Cancelled)

15. (Cancelled)